

# MLM MINI-PRO SERIES

## The Next Generation of Material Lifts

Designed specifically for the rental and construction equipment markets - providing improved specifications, features, durability and performance.

### Higher Productivity

Best in class load capacity and a USA made dual-handle, shift-on-the-fly, two-speed winch, that can raise your load twice as fast as competitive models, lets you complete your jobs faster than ever before.

### Greater Durability

Robust, construction-grade cast metal cable pulleys, heavier-gauge aluminium extrusions, and USA made *Colson® Performa* non-marking casters provide far superior durability and extended service life.

### Single Door Access

Narrow base width and ultra-compact lowered mast height makes it easy to manoeuvre through a single door without having to tilt the machine back.

### Versatile

Forks can be installed below the carriage or in the inverted position for full free lift and maximum height.

### Easy to Use

New and innovative features including the Smart-Set™ “pin-less” height adjustment system for the steering and loading wheels and Clear-Path™, providing foot clearance between the rear transport wheels, are just a few of the many new features provided.

### Easy to Transport

Featuring loading wheels that can be quickly adjusted to various tailgate heights providing easy loading and transport to and from the job site. Can be transported in some vans and SUVs.

### Easy to Store

Tool-less folding legs with integrated, non-marking stowage wheels allows easy, floor friendly manoeuvring in stowed position.

### Standard Features

- Dual-handle, two-speed, shift-on-the-fly winch
- Easily loadable and highly transportable
- Metal cable pulleys with sealed bearings
- Heavy-gauge aluminium extrusions
- USA made *Colson® Performa* casters
- Patent pending Smart-Set™ system
- Clear-Path™ foot clearance
- Non-marking casters and transport wheels
- Highly durable powder coated finish
- Tool-less folding legs
- Non-marking stowage wheels
- Easy-access crane attachment point
- Standard forks
- Exceptional warranty
- Made in the USA

Patents pending

	MLM-16
Lift height	
Standard forks - up	4.9 m
Standard forks - down	4.4 m
Adjustable forks (up)	4.9 m
Adjustable forks (down)	4.4 m
Boom	4.8 m
Height - stowed	1.59
Length - stowed	0.88 m
Length - operating	1.85 m
Width - stowed	0.77 m
Width - stabilizers deployed	1.63 m
Stabilizers	Optional
Forks	
Length	0.76 m
Width (Outside)	0.58 m
Maximum load capacity	
360 mm load centre	295 kg
610 mm load centre	195 kg
1070 mm load centre	79 kg
Ground clearance	0.06 m
Load height - minimum	0.15 m
Weight	135 kg
Winch cranks / distance	
High speed	13.1 cranks / m
Low speed	49.2 cranks / m

### Standard Features



Hold down can be actuated when stabilizers are stowed.



Precision cast metal cable pulleys, folding leg slide pads, non-marking leg wheels and non-marking upper loading wheels.



Patent-pending Smart-Set™ “pin-less” adjustment system and Clear-Path™ foot clearance

### Options & Accessories

- Adjustable forks
- Non-marking forks
- Boom
- Pipe Cradles
- Fork extensions
- Load Platform
- Stabilizers

**LIFTSMART**  
www.liftsmart.net